



**ENGINEERING STRUCTURAL CALCULATIONS**  
**For**  
**Gillette 186"/234" Frame Gensets**

**May 21, 2025**

**186"/234" Frame Genset Models:**  
**SPMI-8000**

**Location: Florida**

**Designed in compliance with: 2023 Florida Building Code, 8th Edition**  
**ASCE 7 - 22 Minimum Design Loads for Buildings and Other Structures**  
**2020 Aluminum Association Design Manual**  
**ANSI/AISC 360-22 - Specification for Structural Steel Buildings**

Anchoring: 1/2" Bolt/Anchors - Minimum (7) per side (14) total

This item has been digitally signed and sealed by Matthew T. Baldwin, P.E. on the date adjacent to the seal. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

---

**Matthew T. Baldwin, P.E.**  
**Florida License #64608**

## Project Information

**Project Name/Model #** - Gillette 186"/234" Frame Gensets  
**Project Number** -  
**Project Description** - Sound Attenuated Generator Enclosure  
**Project Location** - Florida  
**Customer** -  
**Mounting Location** - Ground

## Enclosure Materials

**Roof Beam** - 0.062 Aluminum Truss - 5052-H34  
**Roof Panels** - 0.080 Aluminum Panel - 5052-H34  
**Wall Panels** - 0.080 Aluminum Panel - 5052-H34  
**Base Frame/Skid** - Aluminum Formed Steel 'C' Channel

## Components

**GenSet Manufacturer** - Gillette  
**GenSet Size and Model** - SPMI-8000

Supported by - Base


**Base** - Aluminum Formed Steel 'C' Channel

## Fasteners/Hardware

	Bolt Size	Washer	Nut	Grade/Finish
Roof to Walls	- 5/16" - 18 Bolts	5/16" Washer	Nut Clip	Grade 18-8/SS
Wall to Wall	- 5/16" - 18 Bolts	5/16" Washer	Nut Clip	Grade 18-8/SS
Walls to Base	- 5/16" - 18 Bolts	5/16" Washer	Nut Clip	Grade 18-8/SS
Base to Slab/Tank	- 1/2" Set Bolt Anchors	Flat Washers	Hex Nuts	Grade 5/Galv.

## Specification Requirements

**Wind Speed** - 200 mph  
**Exposure Category** - D  
**Risk Category** - III  
**Ground Snow Load ( $P_g$  Fig 7.1)** - 0 psf  
**Ice Thickness ( $t$  Fig 10-2 to 10-6)** - 0.25 in  
**and Concurrent Wind Gust ( $V_c$ )** - 30 mph  
**Seismic Site Class** - B



Matthew T. Baldwin, P.E.  
Florida License #64608

# Enclosure Dimensions & Component Weights

## Gillette 186"/234" Frame Gensets

Roof Style-     Flat

### Enclosure Dimensions (ft)


Wall	Length (ft)		Height (ft)
1	4.33	x	6.021
2	4.33	x	6.021
3	14.5	x	6.021
4	14.5	x	6.021

### Base Dimensions


Width (Wall 1/2 Side)	=	52	in
Length (Wall 3/4 Side)	=	132	in
Height	=	8	in

### Roof/Eave Information

Roof Pitch Angle	-	( $\theta$ )	=	0.0	Degrees
Eave/Roof Height	-	$h$	=	6.688	



Plan




Elevation

### Structure Areas

Walls 1/2 Area	-	( $w1$ )	=	29.0	ft <sup>2</sup>	=	4,170	in <sup>2</sup>
Walls 3/4 Area	-	( $w3$ )	=	97.0	ft <sup>2</sup>	=	13,964	in <sup>2</sup>
Roof Area	-	( $R$ )	=	62.8	ft <sup>2</sup>	=	9,041	in <sup>2</sup>
Base Side 1/2		( $T1$ )	=	416.0	in			
Base Side 3/4		( $T3$ )	=	1,056.0	in			

### Component Weights (lightest setup for worst case)

Genset	=	4,765	lbs
Enclosure	=	1,270	lbs
Base	=	400	lbs



Matthew T. Baldwin, P.E.  
Florida License #64608


# MWFRS Net Pressures

## Gillette 186"/234" Frame Gensets

### Wind

Analytical Procedure method and Load Combinations from ASCE 7 are utilized in these calculations.

Enclosure Classification	-	Enclosed
Exposure Category	-	D
Basic Wind Speed	(V)	200 mph
Importance Factor (Wind)	(I <sub>w</sub> )	1.15
Wind Directionality Factors	(K <sub>d</sub> )	0.85
Internal Pressure Coefficients	(GC <sub>pi</sub> )	± 0.18
Velocity Pressure Exposure Coefficient	(K <sub>z</sub> )	1.03
Roof Mean Height Above Ground Level	(z)	7.35 ft
Velocity Pressure	(q)	103.12 psf




### Wind Direction 1

	Enclosure							
	Wall #			Roof				
	1	2	3&4	Parallel to Ridge				
				(C <sub>p</sub> )1 (Distance From Windward Edge)				(C <sub>p</sub> )2
	Windward	Leeward	Side	0 to 3.3	3.3 to 6.7	6.7 to 13.4	> 13.4	
Background Response Factor (Q)	0.97	0.97	0.96	0.97				
Gust Effect Factors (G)	0.91	0.91	0.91	0.91				
External Pressure Coefficients (C <sub>p</sub> )	0.80	-0.233	-0.70	-0.90	-0.90	-0.50	-0.3	-0.18
Net Pressures with + (GC <sub>pi</sub> ) - psf (Net <sub>p+</sub> )	56.7	-40.4	-83.9	-103.2	-103.2	-65.6	-46.8	-35.5
Net Pressures with - (GC <sub>pi</sub> ) - psf (Net <sub>p-</sub> )	93.8	-3.3	-46.8	-66.1	-66.1	-28.5	-9.7	1.6

### Wind Direction 2

	Enclosure							
	Wall #			Roof - Normal To Ridge				
	3	4	1&2	(C <sub>p</sub> )1 (Distance From Windward Edge)				(C <sub>p</sub> )2
	Windward	Leeward	Side	0 to 3.3	> 3.3			
Background Response Factor (Q)	0.96	0.96	0.97	0.96				
Gust Effect Factors (G)	0.91	0.91	0.91	0.91				
External Pressure Coefficients (C <sub>p</sub> )	0.80	-0.5	-0.70	-1.04	-0.70			-0.18
Net Pressures with + (GC <sub>pi</sub> ) - psf (Net <sub>p+</sub> )	56.2	-65.3	-84.4	-115.7	-83.9			-35.4
Net Pressures with - (GC <sub>pi</sub> ) - psf (Net <sub>p-</sub> )	93.3	-28.1	-47.3	-78.6	-46.8			1.8

Plus and minus signs signify pressures acting toward or away from the surfaces, respectively.



Matthew T. Baldwin, P.E.  
Florida License #64608

## Snow

Importance Factor (Snow)	$(I_s)$	1.1
Exposure Factor	$(C_e)$	0.8
Thermal Factor	$(C_t)$	1.2
Slope Factor	$(C_s)$	1.0


Flat Roof Snow Load  $(p_s)$  0 psf

## Seismic

Importance Factor (Seismic)	$(I_{sm})$	1.25	
Mapped Acceleration Parameter	$(S_s)$	0.14	Figures 22-1 Thru 22-14
Mapped Acceleration Parameter	$(S_1)$	0.07	Figures 22-1 Thru 22-14
Site Coefficient	$(F_a)$	1	
Site Coefficient	$(F_v)$	1	
MCE Spectral Resp. Accel. Short Per.	$(S_{MS})$	0.140	
MCE Spectral Resp. Accel. 1-s Period	$(S_{M1})$	0.07	
Design Spectral Accel. Short Period	$(S_{DS})$	0.093	
Design Spectral Accel. 1-s Period	$(S_{D1})$	0.04667	
Fundamental Period of Structure	$(T_a)$	0.077	sec
Long Period Transistion Period	$(T_L)$	8	sec Figure 22-15 Thru 22-20
Seismic Design Category	-	A	
Total Effective Seismic Weight	$(W_{eff})$	7,314	lbs
Response Modification Coefficient	$(R)$	2	Table 12.2-1
System Overstrength Factor	$(\Omega_o)$	2.5	Table 12.2-1
Deflection Amplification Factor	$(C_d)$	2	Table 12.2-1
Seismic Response Coefficient	$(C_s)$	0.058	

## Resultant Seismic Forces

Horizontal Seismic Load Effect	-	$(E_h)$	
Force at Base of Base	=	0.1	kips
Force at Top of Base	=	0.1	kips
Force at Top/Bottom of Enclosure	=	0.013	kips
Force on Silencer	=	0	kips
Vertical Seismic Load Effect $(E_v)$	=	0	(Factor, Used With Deadweight in Load Combinations)



Matthew T. Baldwin, P.E.  
Florida License #64608

# Structural Calculations - Roof

## Gillette 186"/234" Frame Gensets

### Critical Loads & Pressures

#### Wind Pressures

Downforce 1.75 psf = 0.01 psi  
Uplift -115.7 psf = -0.80 psi

#### Snow Pressure

0 psf = 0.000 psi

#### Seismic Load

Horizontal = 13 lbs  
Vertical Factor = 0

#### Roof Live Load

Downforce 20.0 psf = 0.1389 psi or 300 lbs Concentrated Load

Pressures & loads are the numerical maximums to be analyzed for shear, bending tension, and compression.

### Section Properties

0.062 Aluminum Truss - 5052-H34

Cross Sectional Area (A) = 0.30 in<sup>2</sup>  
Moment of Inertia - x (I<sub>x</sub>) = 0.269 in<sup>4</sup>  
Moment of Inertia - y (I<sub>y</sub>) = N/A in<sup>4</sup>  
Section Modulus - x (S<sub>x</sub>) = 0.309 in<sup>3</sup>  
Section Modulus - y (S<sub>y</sub>) = N/A in<sup>3</sup>  
Radius of Gyration - x (r<sub>x</sub>) = 0.942 in  
Radius of Gyration - y (r<sub>y</sub>) = N/A in

Weight (w) = 0.030 lbs/in  
Modulus of Elasticity (E) = 1.02E+04 ksi  
Safety Factor (Ω) = 1.95  
Plastic Section Mod. - x (Z<sub>x</sub>) = 0.18  
Plastic Section Mod. - y (Z<sub>y</sub>) = 0.18  
Tensile Ultimate Strength (F<sub>tu</sub>) = 34 ksi  
Tensile Yield Strength (F<sub>ty</sub>) = 26 ksi  
Compressive Yield Strength (F<sub>cy</sub>) = 24 ksi  
Shear Ultimate Strength (F<sub>su</sub>) = 20 ksi

### Roof Frame Calculations

Member Designed for Forces Acting on the **Strong Axis**


#### Interior Beam Critical Member Dimensions

Interior Beam Length (L<sub>i</sub>) = 42.8 in  
Load Spanned Width (W<sub>i</sub>) = 36.2 in

#### Interior Beam Calculated Forces

##### Distributed Loads

Weight of Beam (w) = 0.029 lbs/in  
Wind Load Downforce (w<sub>d</sub>) = 0.440 lbs/in  
Wind Load Uplift Force (w<sub>u</sub>) = -29.085 lbs/in



Matthew T. Baldwin, P.E.  
Florida License #64608

**Shear Forces (Maximum at End)**

Beam Weight Shear ( $V_b$ ) = 1.75 lbs  
Wind DownForce Shear ( $V_{wd}$ ) = 9.7 lbs  
Wind Uplift Shear ( $V_{wu}$ ) = -664.3 lbs

Total Shear Downward = 11.5 lbs  
Total Shear Upward = 662.5 lbs

Design Shear ( $V_{bi}$ ) = 662.5 lbs

**Stress Forces (Bending)**

Beam Weight Moment ( $M_b$ ) = 11 lb-in  
Wind Downforce Moment ( $M_d$ ) = 47 lb-in  
Wind Uplift Moment ( $M_u$ ) = -3,223 lb-in

Total Moments Downward = 59 lb-in  
Total Moments Upward = 3,211 lb-in

Design Moment ( $M_T$ ) = 3,211 lb-in

Design Stress ( $\sigma_{bi}$ ) = 8,921 psi

**Interior Beam Design Calculations****Allowable Shear Strength**

Slenderness Limit 1 ( $S_1$ ) = -20.08  
Slenderness Limit 2 ( $S_2$ ) = 102.40  
Slenderness Ratio ( $S$ ) = 18.0  
Allowable Shear Stress = 9,856 psi  
Allowable Shear Strength ( $V_n$ ) = 3,548 lbs

**Conclusion**

( $V_{bi}$ ) 663 lbs < ( $V_n$ ) 3,548 lbs **OK**

**Allowable Stresses For Tension And Compression (Bending)****Tension**

Allowable Tensile Stress ( $F_t$ ) = 14,551 psi


**Compression**

Slenderness Limit 1 ( $S_1$ ) = 25.0  
Slenderness Limit 2 ( $S_2$ ) = 125.0  
Slenderness Ratio ( $S$ ) = 41.3  
Allowable Compressive Stress ( $F_c$ ) = 13,121 psi

The Allowable Compressive Stress is the controlling  
Therefore, ( $F_b$ ) = 13,121 psi failure design

**Conclusion**

( $\sigma_{bi}$ ) 8,921 psi < ( $F_b$ ) 13,121 psi **OK**



Matthew T. Baldwin, P.E.  
Florida License #64608

## Entire Roof Uplift Calculations

### Roof Area

Area of Roof Subjected to Uplift  $(R) = 9,041 \text{ in}^2$  (not including discharge hood area)

### Roof Uplift Calculated Forces

Roof Weight  $(w_a) = 102 \text{ lbs}$

Wind Load Uplift Force  $(w_{ru}) = -7,264 \text{ lbs}$

Total Roof Design Uplift  $(W_{ru}) = -7,162 \text{ lbs}$

### Mounting Hardware - Roof Frame to Wall Panels

Screws Along Length - 1 Side = 10 5/16" - 18 Bolts

Screws Along Width - 1 Side = 3 5/16" - 18 Bolts

Total Mounting Screws = 26 5/16" - 18 Bolts

### Entire Roof Uplift Design Calculations

Grade 18-8/SS Ult. Strength = 150,000 psi

5/16" Bolt Nominal Diameter = 0.255 in

5/16" Bolt Effective Area = 0.051 in<sup>2</sup>

5/16" Bolt Threads per Inch = 18

Washer Nominal Diameter = 0.875 in

Wall Panel Tensile Ult. Strength = 34 ksi

Wall Panel Tensile Yield Strength = 26 ksi

Safety Factor = 3

Wall Panel Nominal Thickness = 0.0800 in

Maximum Tensile Strength = 566.7 lbs

Maximum Shear/Bearing Strength = 408.6 lbs

Max. Tensile Load per Bolt = 408.6 lbs

Max. Total Screws Tensile Strength  $(P_{ts}) = 10,623 \text{ lbs}$

### Conclusion

$(W_{ru}) \quad 7,162 \text{ lbs} < (P_{ts}) \quad 10,623 \text{ lbs} \quad \text{OK}$

## Roof Panel Uplift Calculations

### Roof Panel Critical Member Dimensions

Critical Panel Length  $(L_p) = 73.40 \text{ in}$

Critical Panel Width  $(W_p) = 52.00 \text{ in}$

### Roof Panel Uplift Calculated Forces


#### Distributed Loads

Wind Load Uplift Force  $(w_{pu}) = 3,066.6 \text{ lbs}$

### Mounting Hardware - Roof Panel to Roof Frame

Screws Along Length - 1 Side = 3 5/16" - 18 Bolts - Grade 18-8/SS

Screws Along Width - 1 Side = 3 5/16" - 18 Bolts - Grade 18-8/SS



Matthew T. Baldwin, P.E.

Florida License #64608

### Roof Panel Uplift Design Calculations


Grade 18-8/SS Ult. Strength	=	150,000	psi
5/16" Bolt Nominal Diameter	=	0.255	in
5/16" Bolt Effective Area	=	0.051	in <sup>2</sup>
5/16" Bolt Threads per Inch	=	18	
Washer Nominal Diameter	=	0.875	in
Roof Panel Tensile Ult. Strength	=	34	ksi
Roof Panel Tensile Yield Strength	=	26	ksi
Safety Factor	=	3	
Roof Panel Nominal Thickness	=	0.0800	in

	Roof Frame	Z-Bar	(Accounts for screw pull-over and pull-out strengths)
Maximum Tensile Strength	= 566.7	164.4	
Maximum Shear/Bearing Strength	= 408.6	371.1	
Max. Tensile Load per Screw	= 408.6	164.4	

Max. Total Screws Tensile Strength  $(P_{ts}) = 4,903 \text{ lbs}$

### Conclusion

$(w_{pu}) \text{ 3,067 lbs} < (P_{ts}) \text{ 4,903 lbs}$  **OK**



Matthew T. Baldwin, P.E.  
Florida License #64608

# Structural Calculations - Wall Panel

## Gillette 186"/234" Frame Gensets

### Critical Loads & Pressures

#### Walls 1 & 2

Maximum Pressures Acting:

Toward	93.8	psf	=	0.6514	psi
Away	-84.4	psf	=	-0.5861	psi

#### Walls 3 & 4

Maximum Pressures Acting:

Toward	93.3	psf	=	0.6478	psi
Away	-83.9	psf	=	-0.5829	psi

### Roof Forces on Critical Panel (From Roof Frame Calculations)

Maximum Downforce	$(W_d)$	=	1,358	lbs
Wind Load Uplift Force	$(w_{pu})$	=	3,067	lbs

Pressures and weights are the numerical maximums to be analyzed for shear, tension, and compression.

### Critical Wall Panel Dimensions

Critical/Maximum Panel Width	=	52.00	in
Critical/Maximum Panel Height	=	72.00	in

### Section Properties

0.080 Aluminum Panel - 5052-H34

Cross Sectional Area	$(A)$	=	4.11	in <sup>2</sup>
Moment of Inertia - x	$(I_x)$	=	0.048	in <sup>4</sup>
Moment of Inertia - y	$(I_y)$	=	N/A	in <sup>4</sup>
Section Modulus - x	$(S_x)$	=	0.828	in <sup>3</sup>
Section Modulus - y	$(S_y)$	=	N/A	in <sup>3</sup>
Radius of Gyration - x	$(r_x)$	=	0.108	in
Radius of Gyration - y	$(r_y)$	=	N/a	in
Weight	$(w)$	=	0.026	lbs/in <sup>2</sup>
Modulus of Elasticity	$(E)$	=	1.02E+04	ksi
Safety Factor	$(\Omega)$	=	1.67	
Plastic Section Mod. - x	$(Z_x)$	=	0.13	
Plastic Section Mod. - y	$(Z_y)$	=	0.13	
Tensile Ultimate Strength	$(F_{tu})$	=	34	ksi
Tensile Yield Strength	$(F_{ty})$	=	26	ksi
Compressive Yield Strength	$(F_{cy})$	=	24	ksi
Shear Ultimate Strength	$(F_{su})$	=	20	ksi


### Wall Panel Calculations

#### Critical Wall Area

Area of Wall Panel	$(W)$	=	3,744.0	in <sup>2</sup>
--------------------	-------	---	---------	-----------------

#### Mounting Hardware - Roof Frame to Wall Panels

Screws Along Height - 1 Side	=	4	5/16" - 18 Bolts
Screws Along Width - 1 Side	=	8	5/16" - 18 Bolts
Total Mounting Screws	=	24	5/16" - 18 Bolts



Matthew T. Baldwin, P.E.  
Florida License #64608


Grade 5 Ultimate Strength = 150,000 psi  
 5/16" Bolt Nominal Diameter = 0.255 in  
 5/16" Bolt Effective Area = 0.051 in<sup>2</sup>  
 5/16" Bolt Threads per Inch = 18  
 Washer Nominal Diameter = 0.875 in  
 Roof Panel Tensile Ult. Strength = 34 ksi  
 Roof Panel Tensile Yield Strength = 26 ksi  
 Safety Factor = 3  
 Roof Panel Nominal Thickness = 0.0800 in

		Roof Frame	
Maximum Tensile Strength	=	388.7	(Accounts for screw pull-over and pull-out strengths)
Maximum Shear/Bearing Strength	=	300.0	
Max. Tensile Load per Bolt	=	300.0	

Max. Total Screws Tensile Strength ( $P_{ts}$ ) = 6,391 lbs

**Conclusion**

( $w_{pu}$ ) 2,439 lbs < ( $P_{ts}$ ) 6,391 lbs **OK**




---

Matthew T. Baldwin, P.E.  
Florida License #64608

# Structural Calculations - Enclosure to Base

## Gillette 186"/234" Frame Gensets

### Critical Pressures & Loads

To determine maximum moment forces, pressures are algebraically combined relative to toward or away forces (+ & -) and each wind direction.

#### Wind Direction 1

To be conservative, roof downforce is neglected.

##### Net Pressures with + Internal Pressure(+Gcpi)

Walls 1 & 2	-	97.1	psf =	0.6743	psi
Wall 3 or 4	-	83.9	psf =	0.5829	psi
Roof Uplift	-	103.2	psf =	0.7167	psi

##### Net Pressures with - Internal Pressure(-Gcpi)

Walls 1 & 2	-	97.1	psf =	0.6743	psi
Wall 3 or 4	-	46.8	psf =	0.3251	psi
Roof Uplift	-	66.1	psf =	0.4589	psi

#### Wind Direction 2

##### Net Pressures with + Internal Pressure(+Gcpi)

Walls 3 & 4	-	121.4	psf =	0.8432	psi
Wall 1 or 2	-	84.4	psf =	0.5861	psi
Roof Uplift	-	115.7	psf =	0.8034	psi

##### Net Pressures with - Internal Pressure(-Gcpi)

Walls 3 & 4	-	121.4	psf =	0.8432	psi
Wall 1 or 2	-	47.3	psf =	0.3283	psi
Roof Uplift	-	78.6	psf =	0.5456	psi

### Seismic

Horizontal Seismic Force (E<sub>h</sub>) = 13 lbs

### Enclosure Critical Dimensions & Weights

Total Enclosure Weight	(W <sub>t</sub> )	=	6,035.0	lbs	(Includes all components)
Walls 1/2 Area	-	(w1)	=	4169.9	in <sup>2</sup>
Walls 3/4 Area	-	(w3)	=	13963.8	in <sup>2</sup>
Roof Area	-	(R)	=	9041.0	in <sup>2</sup>


### Enclosure Calculated Forces

#### Maximum Wind Load Forces on Walls

##### Wind Direction 1

##### Net Forces with + Internal Pressure(+Gcpi)

Walls 1/2	-	=	2,812	lbs
Wall 3 or 4	-	=	8,140	lbs
Roof Uplift	-	=	6,479	lbs



Matthew T. Baldwin, P.E.  
Florida License #64608

**Net Forces with - Internal Pressure(-Gcpi)**

Walls 1/2	-	=	2,812	lbs
Wall 3 or 4	-	=	4,540	lbs
Roof Uplift	-	=	4,149	lbs

**Wind Direction 2****Net Forces with + Internal Pressure(+Gcpi)**

Walls 3/4	-	=	11,774	lbs
Wall 1 or 2	-	=	2,444	lbs
Roof Uplift	-	=	7,264	lbs

**Net Forces with - Internal Pressure(-Gcpi)**

Walls 3/4	-	=	11,774	lbs
Wall 1 or 2	-	=	1,369	lbs
Roof Uplift	-	=	4,933	lbs

**Enclosure Overturn Forces (Includes Seismic)**

(Postive forces act upward, negative forces act downward)

**Wind Direction 1****Net Forces with + Internal Pressure(+Gcpi)**

Overturn on Walls 1/2	=	871	lbs
Overturn on Walls 3/4	=	6,508	lbs

**Net Forces with - Internal Pressure(-Gcpi)**

Overturn on Walls 1/2	=	-295	lbs
Overturn on Walls 3/4	=	2,563	lbs

**Wind Direction 2****Net Forces with + Internal Pressure(+Gcpi)**

Overturn on Walls 3/4	=	9,707	lbs
Overturn on Walls 1/2	=	1,178	lbs

**Net Forces with - Internal Pressure(-Gcpi)**

Overturn on Walls 3/4	=	8,542	lbs
Overturn on Walls 1/2	=	-235	lbs

Design Overturn Force ( $O_E$ ) = 9,707 lbs Acting On Wall 3/4

**Mounting Hardware - Enclosure to Base/Tank or Pad**

To be conservative, bolt connections along the adjacent walls are neglected.

No. of Bolt Connections Along Wall 3/4 = 8 5/16" - 18 Bolts - Grade 18-8/S


**Enclosure Overturn Design Calculations**

Grade 18-8 Ultimate Strength	=	150,000	psi
Grade 8.8 Nom. Tensile Stress	=	112,500	psi (Includes Reduction Factor)
5/16" Bolt Effective Area	=	0.051	in <sup>2</sup>
Tensile Strength per Bolt	=	2,873	lbs

Total Bolts Tensile Strength = 22,982 lbs

**Conclusion**

( $O_E$ ) 9,707 lbs < ( $R_v$ ) 22,982 lbs **OK**



Matthew T. Baldwin, P.E.  
Florida License #64608

# Structural Calculations - Enclosure With Base/Tank to Pad

## Gillette 186"/234" Frame Gensets

### Critical Wind Load Pressures

To determine maximum moment forces, pressures are algebraically combined relative to toward or away forces (+ & -) and each wind direction.

#### Wind Direction 1

To be conservative, roof downforce is neglected.

##### Net Pressures with + Internal Pressure(+G<sub>cpi</sub>)

Walls 1 & 2	-	97.1	psf =	0.6743	psi
Wall 3 or 4	-	83.9	psf =	0.5829	psi
Roof Uplift	-	103.2	psf =	0.7167	psi

##### Net Pressures with - Internal Pressure(-G<sub>cpi</sub>)

Walls 1 & 2	-	97.1	psf =	0.6743	psi
Wall 3 or 4	-	46.8	psf =	0.3251	psi
Roof Uplift	-	66.1	psf =	0.4589	psi

#### Wind Direction 2

##### Net Pressures with + Internal Pressure(+G<sub>cpi</sub>)

Walls 3 & 4	-	121.4	psf =	0.8432	psi
Wall 1 or 2	-	84.4	psf =	0.5861	psi
Roof Uplift	-	115.7	psf =	0.8034	psi

##### Net Pressures with - Internal Pressure(-G<sub>cpi</sub>)

Walls 3 & 4	-	121.4	psf =	0.8432	psi
Wall 1 or 2	-	47.3	psf =	0.3283	psi
Roof Uplift	-	78.6	psf =	0.5456	psi

### Seismic

Enclosure Horiz. Seismic Force (E<sub>Eh</sub>) = 13 lbs

Base/Tank Horiz. Seismic Force (E<sub>Bh</sub>) = 73 lbs

### Enclosure With Base/Tank Critical Dimensions & Weights

Total Enclosure Weight	(W <sub>t</sub> )	=	6,435	lbs	(Includes all components)
Walls 1/2 Area	-(w <sub>1</sub> )	=	4,586	in <sup>2</sup>	(Includes Base/Tank Surface Area)
Walls 3/4 Area	-(w <sub>3</sub> )	=	15,020	in <sup>2</sup>	(Includes Base/Tank Surface Area)
Roof Area	-(R)	=	9,041	in <sup>2</sup>	


### Enclosure With Base/Tank Calculated Forces

#### Maximum Wind Shear Forces on Walls Including Base/Tank

##### Wind Direction 1

##### Net Forces with + Internal Pressure(+G<sub>cpi</sub>)

Walls 1/2	-	=	3,092	lbs
Wall 3 or 4	-	=	8,755	lbs
Roof Uplift	-	=	6,479	lbs



Matthew T. Baldwin, P.E.  
Florida License #64608

**Net Forces with - Internal Pressure(-Gcpi)**

Walls 1/2	-	=	3,092	lbs
Wall 3 or 4	-	=	4,883	lbs
Roof Uplift	-	=	4,149	lbs

**Wind Direction 2****Net Forces with + Internal Pressure(+Gcpi)**

Walls 3/4	-	=	12,664	lbs
Wall 1 or 2	-	=	2,688	lbs
Roof Uplift	-	=	7,264	lbs

**Net Forces with - Internal Pressure(-Gcpi)**

Walls 3/4	-	=	12,664	lbs
Wall 1 or 2	-	=	1,505	lbs
Roof Uplift	-	=	4,933	lbs

Enclosure with Base/Tank Maximum Wind Force = 12,664 lbs Acting On Wall 3/4

Coefficient of Friction - Steel to Wet Concrete ( $\mu_s$ ) = 0.45

Frictional Resisting Force (Total Weight x  $\mu_s$ ) = 2,896

Enclosure with Base/Tank Design Shear ( $V_{EB}$ ) = 9,769

**Enclosure With Base/Tank Overturn Forces (Includes Seismic)**

Postive forces act upward

**Wind Direction 1****Net Forces with + Internal Pressure(+Gcpi)**

Overturn on Walls 1/2	=	816	lbs
Overturn on Walls 3/4	=	7,490	lbs

**Net Forces with - Internal Pressure(-Gcpi)**

Overturn on Walls 1/2	=	-349	lbs
Overturn on Walls 3/4	=	3,037	lbs


**Wind Direction 2****Net Forces with + Internal Pressure(+Gcpi)**

Overturn on Walls 3/4	=	11,202	lbs
Overturn on Walls 1/2	=	1,106	lbs

**Net Forces with - Internal Pressure(-Gcpi)**

Overturn on Walls 3/4	=	10,037	lbs
Overturn on Walls 1/2	=	-359	lbs

Design Overturn Force ( $O_{EB}$ ) = 11,202 lbs Acting On Wall 3/4



Matthew T. Baldwin, P.E.  
Florida License #64608

### Mounting Hardware - Enclosure With Base/Tank to Pad

No. of Bolt Connections Along Wall 3/4 = 7 Bolts 1/2" Set Bolt Anchors - Grade 5/Galv.

### Enclosure With Base/Tank Design Calculations

#### Mounting Hardware - Shear and Tension

Grade 5 Ultimate Stress = 120,000 psi  
Grade 5 Nom. Shear Stress = 48,000 psi  
Grade 5 Nom. Tensile Stress = 90,000 psi  
1/2" Bolt Nominal Area = 0.159 in<sup>2</sup>  
Shear Strength per Bolt = 3,816 lbs  
Tensile Strength per Bolt = 7,155 lbs  
Avail. Tensile Strength per Bolt = 1,781 lbs (Combined Tension and Shear)

Total Bolts Shear Strength ( $R_{vb}$ ) = 26,712 lbs  
Total Bolts Tensile Strength ( $R_{tb}$ ) = 12,466 lbs


#### Conclusion

##### Shear

( $V_{EB}$ ) 9,769 lbs < ( $R_{tb}$ ) 26,712 lbs **OK**

##### Tension

( $O_{EB}$ ) 11,202 lbs < ( $R_{tb}$ ) 12,466 lbs **OK**



Matthew T. Baldwin, P.E.  
Florida License #64608