



# GILLETTE GENERATORS

## LIQUID COOLED NAT. GAS ENGINE GENERATOR SET

PRIME MODEL

# PR-800

60 HERTZ

Model	HZ	PRIME 105°C RISE	
		LIQUID PROPANE	NATURAL GAS
<b>PR-800-60 HERTZ</b>	60	80	80



All generator sets are USA prototype built and thoroughly tested. Production models are USA factory built and 100% load tested.



**UL1446, UL508, UL142, UL498**



**NFPA 110, 99, 70, 37**

All generator sets meet NFPA-110 Level 1, when equipped with the necessary accessories and installed per NFPA standards.



**NEC 700, 701, 702, 708**



**NEMA ICS10, MG1, ICS6, AB1**



**ANSI C62.41, 27, 59, 32, 480, 40Q, 81U, 360-05**




**ASCE 7-22**

All generator sets meet 200 MPH rating.




**EPA 40CFR Part 60, 1048, 1065, 1068**



### “OPEN” GEN-SET

There is no enclosure, so gen-set must be placed within a weather protected area, un-inhabited by humans or animals, with proper ventilation. Silencer not supplied, as installation requirements are not known. However, this item is available as optional equipment.



### “LEVEL 2” HOUSED GEN-SET

Full aluminum weather protection and superior sound attenuation for specific low noise applications. Critical grade muffler is standard.

### GENERATOR RATINGS

GENERATOR RATINGS					LIQUID PROPANE		NATURAL GAS FUEL	
GENERATOR MODEL	VOLTAGE		PH	HZ	105°C RISE PRIME RATING		105°C RISE PRIME RATING	
	L-N	L-L			KW/KVA	AMP	KW/KVA	AMP
PR-800-1-1	120	240	1	60	80/80	333	80/80	333
PR-800-3-2	120	208	3	60	80/100	278	80/100	278
PR-800-3-3	120	240	3	60	80/100	241	80/100	241
PR-800-3-4	277	480	3	60	80/100	120	80/100	120

RATINGS: All single phase gen-sets are dedicated 4 lead windings, rated at unity (1.0) power factor. All three phase gen-sets are 12 lead windings, rated at (.8) power factor. 105°C “PRIME RATINGS” are strictly for gen-sets provide the prime source of electric power, where normal utility power is unavailable or unreliable. A 10% overload is allowed for a total of 1 hour, within every 12 hours of operation of PRIME RATED systems. All gen-set power ratings are based on temperature rise measured by resistance method as defined by MIL-STD 705C and IEEE STD 115, METHOD 6.4.4. All generators have class H (180°C) insulation system on both rotor and stator windings. All factory tests and KW/KVA charts shown above are based on 105°C (prime) R/R winding temperature, within a maximum 40°C ambient condition. Specifications & ratings are subject to change without prior notice.

# APPLICATION AND ENGINEERING DATA FOR MODEL PR-800-60 HZ

## GENERATOR SPECIFICATIONS

Manufacturer..... Stamford Electric Generators  
Model & Type.....UCI274C-06, 4 Pole, 4 Lead, Single Phase  
.....UCI274D-311, 4 Pole, 12 Lead, Three Phase  
.....UCI274D-17, 4 Pole, 12 Lead, Three Phase  
Exciter..... Brushless, shunt excited  
Voltage Regulator.....Solid State, HZ/Volts  
Voltage Regulation..... ½%, No load to full load  
Frequency..... Field convertible, 60 HZ to 50 HZ  
Frequency Regulation..... ½% (½ cycle, no load to full load)  
Unbalanced Load Capability..... 100% of prime amps  
Total Stator and Load Insulation..... Class H, 180°C  
Temperature Rise..... 105°C R/R, prime rating @ 40°C amb.  
1 Ø Motor Starting @ 30% Voltage Dip (240V)..... 265 kVA  
3 Ø Motor Starting @ 30% Voltage Dip (208-240V) .... 400 kVA  
3 Ø Motor Starting @ 30% Voltage Dip (480V)..... 520 kVA  
Bearing..... 1, Pre-lubed and sealed  
Coupling..... Direct flexible disc  
Total Harmonic Distortion.....Max 3 | % (MIL-STD705B)  
Telephone Interference Factor.....Max 50 (NEMA MG1-22)  
Deviation Factor.....Max 5% (MIL-STD 405B)  
Ltd. Warranty Period.....24 Months from date of start-up or  
..... 1000 hours use, first to occur.

## GENERATOR FEATURES

- World Renown Stamford Electric Generator having UL-1446 certification.
- Full generator protection with **Deep Sea 7420** controller, having UL-508 certification.
- Automatic voltage regulator with over-excitation, under-frequency compensation, under-speed protection, and EMI filtering. Entire solid-state board is encapsulated for moisture protection.
- Generator power ratings are based on temperature rise, measured by resistance method, as defined in MIL-STD 705C and IEEE STD 115, Method 6.4.4.
- Power ratings will not exceed temperature rise limitation for class H insulation as per NEMA MG1-22.40.
- Insulation resistance to ground, exceeds 1.5 meg-ohm.
- Stator receives 2000 V. hi-potential test on main windings, and rotor windings receive a 1500 V. hi-potential test, as per MIL-STD 705B.
- Full amortisseur windings with UL-1446 certification.
- Complete engine-generator torsional acceptance, confirmed during initial prototype testing.
- Full load testing on all engine-generator sets, before shipping.
- Self ventilating and drip-proof & revolving field design

## ENGINE SPECIFICATIONS AND APPLICATIONS DATA

### ENGINE

Manufacturer..... Power Solutions Inc. (PSI)  
Model and Type..... Ind, Power Train, Vortec, 8.8L, 4 cycle  
Aspiration..... Naturally  
Cylinder Arrangement..... 8 Cylinders, V-8  
Displacement Cu. In. (Liters)..... 537 (8.8)  
Bore & Stroke In. (Cm.)..... 4.35 x 4.50 (11.5 x 11.4)  
Compression Ratio..... 10.1:1  
Main Bearings & Style.....5, Bi-Metal Steel and Aluminum  
Cylinder Head..... Cast Iron  
Pistons.....Cast Aluminum  
Crankshaft..... Nodular Iron  
Exhaust Valve..... Inconel, A193  
Governor.....Electronic  
Frequency Reg. (no load-full load).....Isochronous  
Frequency Reg. (steady state).....± 1/4%  
Air Cleaner..... Dry, Replaceable Cartridge  
Engine Speed..... 1800  
Piston Speed, ft/min (m./min)..... 1311 (399)  
Max Power, bhp (kwm) Prime/NG..... 126 (94)  
Ltd. Warranty Period..... 12 Months or 2000 hrs., first to occur

### FUEL SYSTEM

Type..... NAT. GAS, Vapor Withdrawal  
Fuel Pressure (kpa), in. H<sub>2</sub>O.....(1.74), 7”  
Secondary Fuel Regulator.....NG or LPG Vapor System  
Auto Fuel Lock-Off Solenoid.....Standard on all sets  
Fuel Supply Inlet Line.....1¼” NPTF

### FUEL CONSUMPTION

LP GAS: FT <sup>3</sup> /HR (M <sup>3</sup> /HR)	STANDBY
100% LOAD	556.75 (15.75)
75% LOAD	431 (12.20)
50% LOAD	306 (8.66)
LPG = 2500 BTU X FT <sup>3</sup> /HR = Total BTU/HR LPG Conversion: 8.50 FT <sup>3</sup> = 1 LB. : 36.4 FT <sup>3</sup> = 1 GAL.	

NAT. GAS: FT <sup>3</sup> /HR (M <sup>3</sup> /HR)	PRIME
100% LOAD	1330 (37.6)
75% LOAD	1030 (29.1)
50% LOAD	730 (20.6)
NG = 1000 BTU X FT <sup>3</sup> /HR = Total BTU/HR	

### OIL SYSTEM

Type..... Full Pressure  
Oil Pan Capacity qt. (L)..... 8.5 (8.0)  
Oil Pan Cap. W/ filter qt. (L)..... 9.0 (8.5)  
Oil Filter..... 1, Replaceable Spin-On

### ELECTRICAL SYSTEM

Ignition System.....Electronic  
Eng. Alternator and Starter:  
Ground..... Negative  
Volts, DC.....12  
Recommended Battery to -18°C (0°F): .....12 VDC, Size BCI# 27,  
Max Dimensions: .....12” lg X 6 3/4” wi X 9” hi, with standard  
round posts. Min output at 700 CCA. Battery tray (max. dim. at 12”lg  
x 7”wi), hold down straps, battery cables, and battery charger, is  
furnished. Installation of (1) starting battery is required, with possible

higher AMP/HR rating, as described above, if normal environment averages -13°F (-25°C) or cooler.

## APPLICATION AND ENGINEERING DATA FOR MODEL PR-800-60 HZ

### COOLING SYSTEM

Type of System.....Pressurized, closed recovery  
Coolant Pump ..... Pre-lubricated, self-sealing  
Cooling Fan Type (no. of blades).....Pusher (12)  
Fan Diameter inches (cm) ..... 23.6" (599)  
Ambient Capacity of Radiator °F (°C).....125 (51.6)  
Engine Jacket Coolant Capacity Gal (L) .....3.6 (13.7)  
Radiator Coolant Capacity Gal. (L).....5.6 (25.5)  
Maximum Restriction of Cooling Air Intake  
and discharge side of radiator in. H<sub>2</sub>O (kpa) ..... 0.5 (.125)  
Water Pump Capacity gpm (L/min) ..... 33 (125)  
Heat Reject Coolant: Btu/min (kw)..... 7320 (129)  
Low Radiator Coolant Level Shutdown.....Standard  
Note: Coolant temp. shut-down switch setting at 212°F (100°C) with 50/50  
(water/antifreeze) mix.

### AIR REQUIREMENTS

Combustion Air, cfm (m<sup>3</sup>/min) .....314 (8.9)  
Radiator Air Flow cfm (m<sup>3</sup>/min).....12,000 (340)  
Heat Rejected to Ambient:  
Engine: kw (btu/min).....24.9 (1476)  
Alternator: kw (btu/min) ..... 16 (912)

### EXHAUST SYSTEM

Exhaust Outlet Size .....3.5"  
Max. Back Pressure, in. hg (KPA). .....3.0 (10.2)  
Exhaust Flow, at rated kw: cfm (m<sup>3</sup>/min).....1063 (30.1)  
Exhaust Temp., at rated kw: °F (°C) .....1300 (704)  
Engines are EPA certified for LPG and Natural Gas.

### SOUND LEVELS MEASURED IN dB(A)

	Open Set	Level 2 Encl.
Level 2, Critical Silencer .....	88	81

Note: Open sets (no enclosure) has (3) optional silencer system choices due to unknown job-site applications. Level 2 enclosure has installed critical silencer with upgrade to hospital silencer. Sound tests are averaged from several test points and taken at 23 ft. (7 m) from source of noise at normal operation.

### DERATE GENERATOR FOR ALTITUDE

3% per 1000 ft.(305m) above 3000 ft. (914m) from sea level

### DERATE GENERATOR FOR TEMPERATURE

2% per 10°F(5.6°C) above 85°F (29.4°C)

### DIMENSIONS AND WEIGHTS

	Open Set	Level 2 Enclosure
Length in (cm) .....	98 (248)	122 (310)
Width in (cm).....	48 (122)	48 (122)
Height in (cm).....	64 (163)	72.5 (183)
1 Ø Net Weight lbs (kg).....	2684 (1217)	3484 (1580)
1 Ø Ship Weight lbs (kg).....	2874 (1303)	3734 (1694)
3 Ø Net Weight lbs (kg).....	2624 (1190)	3444 (1562)
3 Ø Ship Weight lbs (kg).....	2814 (1276)	3694 (1676)

## DEEP SEA 7420MKII DIGITAL MICROPROCESSOR CONTROLLER

### Deep Sea 7420MKII



The “7420MKII” controller is an auto start mains (utility) failure module for single gen-set applications. This controller includes a backlit LCD display which continuously displays the status of the engine and generator at all times.

The “7420MKII” controller will also monitor speed, frequency, voltage, current, oil pressure, coolant temp., and fuel levels. These modules have been designed to display warning and shut down status. It also includes: (11) configurable inputs • (8) configurable outputs • voltage monitoring • mains (utility) failure detection

• (250) event logs • configurable timers • automatic shutdown or warning during fault detection • remote start (on load) • engine preheat • advanced metering capability • hour meter • text LCD 132 x 64 pixel ratio display • protected solid state outputs • test buttons for: stop/reset • manual mode • auto mode • lamp test • start button • power monitoring (kWh, kVAr, kVAh, kVArh) • IP65 rating (with supplied gasket)

This controller includes the expansion features including RS232, RS484 (using MODBUS-RTU/TCP), direct USB connection with PC, expansion optioned using DSENet for remote annunciation and remote relay interfacing for a distance of up to 3300FT. The controller software is freely downloadable from the internet and allows monitoring with direct USB cable, LAN, or by internet via the built in web interface.

# STANDARD FEATURES FOR MODEL PR-800-60 HZ

## STANDARD FEATURES

### CONTROL PANEL:

Deep Sea 7420 digital microprocessor with logic allows programming in the field. Controller has:

- STOP-MANUAL-AUTO modes and automatic engine shutdowns, signaled by full text LCD indicators:
- Low oil pressure
- High engine temp
- Low Radiator Level
- Three auxiliary alarms
- Battery fail alarm
- Engine fail to start
- Engine over speed
- Engine under speed
- Over & under voltage

Also included is tamper-proof engine hour meter

### ENGINE:

Full flow oil filter • Air filter • Oil pump • Solenoid type starter motor • Hi-temp radiator • Jacket water pump • Thermostat • Pusher fan and guard • Exhaust manifold • Residential Silencer • 12 VDC battery charging alternator • Flexible exhaust connector • "Isochronous" duty, electronic governor • Secondary dry fuel regulator • Dry fuel lock-off solenoid • Vibration isolators • Closed coolant recovery system with 50/50 water to anti-freeze mixture • flexible oil & radiator drain hose.

Design & specifications subject to change without prior notice. Dimensions shown are approximate. Contact Gillette for certified drawings. DO NOT USE DIMENSIONS FOR INSTALLATION PURPOSES.

### AC GENERATOR SYSTEM:

AC generator • Shunt excited • Brushless design • Circuit Breaker installed and wired to gen-set • Direct connection to engine with flex disc • Class H, 180°C insulation • Self ventilated • Drip proof construction • UL Certified

### VOLTAGE REGULATOR:

½% Voltage regulation • EMI filter • Under-speed protection • Over-excitation protection • total encapsulation

### DC ELECTRICAL SYSTEM:

Battery tray • Battery cables • Battery hold down straps • 2-stage battery float charger with maintaining & recharging automatic charge stages

### WEATHER/SOUND PROOF ALUMINUM HOUSING CORROSION RESISTANT PROTECTION CONSISTING OF:

- 9 Heated And Agitated Wash Stages.
- Zinc Phosphate Etching-coating Stage
- Final Baked On Enamel Powder Coat
- 18/8 Stainless Steel Hardware

